
University of Kentucky Research Foundation

- Next Generation Coal Ash Beneficiation Processing Plant addressing entire coal utilization by-product (CUB) stream and producing a variety of value-added products.
- Helps meet Climate Change goals: reduces emissions in cement manufacturing.
- Total Project funding: \$8.9 million (DOE share: \$4.4 million).







A CCPI Round 1 Project

Background

- University of Kentucky Research Foundation will demonstrate an advanced coal-ash beneficiation processing plant that represents next generation in coal utilization.
- Project Location: Ghent Power Station, Ghent, KY.
- Team members:
 - LG&E Energy Corporation, Louisville, KY
 - University of Kentucky Center for Applied Energy Research, Lexington, KY
 - Potential 3rd party participation



Background

- Process generates a range of useful products including:
 - Pozzolan, a product that can replace up to 30% of Portland cement used to make concrete.
 - Lightweight aggregate suitable for use in concrete masonry units such as blocks.
 - A graded fill-sand for construction applications.
 - Unburned carbon product used as a supplemental fuel.
 - Very fine-sized material (~ 3-4 micron median particle size) suitable for use as a polymer filler or specialized pozzolan.

Technology Uniqueness

- University of Kentucky process for producing pozzolan used in concrete, achieves better concrete strength and performance, and can be used at higher substitution levels (30% vs. 20%).
- Process addresses entire coal utilization by-product (CUB) stream with a target of total CUB utilization and can use existing disposal pond ash.
- Process is based on hydraulic classification and froth flotation technology developed at University of Kentucky Center for Applied Energy Research.
- This project generates a range of high-value and consistent quality products from waste ash.



Schedule

NEPA Process

EA, FONSI expected by July 2004

Design

To be determined

Construction

To be determined

Commissioning and Startup

To be determined



Potential Benefits

- A beneficial use for ash stored in power plant ashsettling ponds across U.S. will be demonstrated, reducing need for new ponds, extending life of existing ponds, and potentially eliminating need for new ponds.
- Pozzolan production (156,000 tons per year) will be used to replace an equivalent amount of Portland cement resulting in significant greenhouse gas offset. Portland cement manufacture results in release of ~1 ton of CO₂ per ton of cement produced. Current operations release ~47 million tons per year in U.S. Use of coal ash in cement manufacturing is a pathway for reducing future CO₂ emissions.

